

BCS-V-EIP28FSR3-Ai2(2)



Index: 12168
GTIN13/EAN13: 5904890712782

URL: <https://bcs.pl/gb/8mpx/3919-bcs-v-eip28fsr3-ai22-5904890712782.html>



Product Details

Product	BCS-V-EIP28FSR3-Ai2(2)
Brand	BCS VIEW
Camera type	Dome
Resolution	8 Mpx
Sensor	1/1.8" CMOS
Scanning system	Progressive Scan
Pixels	3840(H)×2160(V)
Lens	fixed
Focal length	2.8 mm
Aperture	F 1.0
Focus	fixed
Iris	fixed
Angle of view	H: 109° V: 56° D: 134°
DORI	Detect 89m / Observe 35m / Recognize 17m / Identify 8m
Min illumination	0.0008Lux(F1.0, AGC) 0Lux(B/W,IR)
S/N ratio	52dB
White balance	(AWB) Auto / manual
WDR	120dB
Backlight compensation	BLC / HLC / WDR(120dB)

Shutter	Auto / manual 1/3~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	3D DNR
Image rotate	Mirror
Stream support	3
Resolutions	8M(3840×2160) / 6M(3200×1800) / 4M(2688×1520) / 2M(1920×1080) / 720P(1280×720) / VGA(640×480) / 360P(640×360)
Main stream	3840×2160@25fps 3200×1800@30fps 2688×1520@30fps 1920×1080@30fps 1280×720@30fps
Second stream	1280×720@30fps 640×480@30fps 640×360@30fps
Third stream	1920×1080@10fps 1280×720@10fps 640×480@10fps 640×360@10fps
Bitrate	32Kbps~16Mbps
Video compression	H.265 / H.265+ / H.264 / H.264+ / MJPEG
Day/night	ICR
Illuminator type	IR
Illuminator	30m
Microphone	Yes
Audio compression	G.711ulaw / G.711alaw / G.722.1 / G.726 / MP2L2 / PCM / MP3 / AAC
Storage	FTP, NAS
Memory card slot	microSD do 512GB
Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	Yes
Privacy masking	4
Network	RJ-45 10/100 Mbps
Compatibility	ONVIF(S/G/T)
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, SRTP, SFTP
Network security	HTTPS, SSL, TLS, IEEE802.1X, Digest authentication, IP address filtering, host authentication (MAC address), CA Certificate, Login Auth/Account Lockout
Power supply type	12V DC / PoE (802.3af)
Power consumption	max 8W
Housing color	White
IP class	IP67
Working environment	-30°C~+60°C max 95% RH
Dimensions	Ø138.3×115.4mm
Weight	0.77 kg
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - Perimeter protection	Crossline, intrusion
Ai - Human/vehicle detection	Human/vehicle classification for crossline and intrusion reduces false alarms
Ai - Face detection	Face detection and tracking, snapshot

Accessories




BCS-V-ADE



BCS-V-UDE



BCS-ADU-B



BCS-ADU170