




Cloud Gateway Max

UCG-Max



*5V DC, 5A USB-C adapter included.



Mechanical

Dimensions 141.8 x 127.6 x 30 mm (5.6 x 5 x 1.2")

Weight 519 g (1.1 lb)

Enclosure material Polycarbonate

Hardware

Processor Quad-core ARM® Cortex®-A53 at 1.5 GHz

System memory 3 GB DDR4

On-board storage 512 GB NVMe SSD

Management interface	Ethernet Bluetooth
Networking interface	LAN: (4) 1/2.5 GbE RJ45 ports WAN: (1) 1/2.5 GbE RJ45 port
IDS/IPS throughput	1.5 Gbps* *Measured with iPerf3 on a DHCP network. Performance may be reduced with PPPoE depending on ISP implementation.
Power method	USB type C (5V DC/5A)
Supported voltage range	100-240V AC
Max. power consumption	16.1W
LCM display	0.96" status display
Button	Factory reset
Ambient operating temperature	-10 to 40° C (14 to 104° F)
Ambient operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

Gateway Features

Performance	Redundant WAN with failover and load balancing WiFi QoS with UniFi APs Application, domain, and country-based QoS Application and device type identification Additional internet failover with LTE Backup Internet quality and outage reporting
Next-generation security	Application-aware firewall rules Signature-based IPS/IDS threat detection Content, country, domain, and ad filtering VLAN/subnet-based traffic segmentation Full stateful firewall
Advanced networking	License-free SD-WAN WireGuard, L2TP and OpenVPN server OpenVPN client OpenVPN and IPsec site-to-site VPN One-click Teleport and Identity VPN Policy-based WAN and VPN routing DHCP relay Customizable DHCP server

Advanced networking

IGMP proxy
IPv6 ISP support

LEDs

Ethernet

Green: link/activity

Application Requirements

Mobile app

UniFi iOS™ and Android™: Version 10.17.2 and later